



CB3000 Client Bridge

Wireless LAN interface for Ethernet devices



FEATURES

IEEE 802.11a/b/g

Flexibility to connect to multiple network technologies

Multi-client support

Affordable connectivity for up to 16 client devices

POS Support

Cost-effective wireless deployment of the market leading point-of-sale devices (IBM, NEC, and more)

IBM POS protocol support

Cost-effective wireless deployment for point-of-sale devices

WEP 40/128, WPA and AES encryption; 802.1x support with PEAP, EAP/TLS, EAP/TTLS authentication

Provides rigorous security for your data and network

Simple, cost-effective high performance wireless connectivity for printers, point-of-sale and Ethernet-enabled devices

The CB3000 provides a robust wireless connection for your Ethernet-enabled devices — from printers, scales, medical equipment, and manufacturing machinery to time clocks, point-of-sale devices and more. The need to extend wiring is eliminated, reducing the cost and complexity of deployment for devices without a PCMCIA or PCI card slot. And the ability to update the firmware provides the investment protection you need, ensuring that the CB3000 meets your networking needs today as well as tomorrow.

Increase productivity throughout your enterprise

The CB3000 allows you to cost-effectively extend the availability of applications, devices, and real-time data, resulting in a productivity increase throughout your enterprise. The ability to move information from time clocks directly into your payroll application eliminates time spent manually processing time cards. The ability to collect statistics from manufacturing machinery enables early identification and resolution of equipment problems — before they impact yield. And the wireless connection enables network changes to be executed quickly and easily, as needed — for example, to connect point-of-sale devices to support a sale in a specific area of the store.

Easy to deploy and manage with enterprise functionality

The CB3000 offers the simplicity of true plug-and-play deployment — minimal configuration is required. Your wireless client devices enjoy uninterrupted connectivity — the CB3000 can easily roam to another access port or access point as needed. And a secure internal web server provides the convenience of anywhere anytime management through any standard web browser.

A secure, reliable, easy-to-move connection

The CB3000 provides the enterprise-class security you need — advanced encryption and authentication mechanisms protect your network and data from unauthorized users. And wireless connectivity offers maximum flexibility. Equipment can be easily moved as needed to accommodate seasonal requirements as well as line and staffing changes, without the time and expense of re-wiring.

Connect up to 16 devices in nearly any environment

The robust mechanical design and support for a wide range of temperatures delivers reliable performance throughout your enterprise, from your front office to the retail, warehouse or factory floor. And when used in conjunction with an Ethernet hub, a single CB3000 can connect up to 16 client devices to your Motorola wireless switches, access ports and access points, making the CB3000 an outstanding value.

SPECIFICATION SHEET

CB3000 CLIENT BRIDGE
Wireless LAN interface for Ethernet devices

Embedded secure web server

Convenient anytime anywhere management

SNMP v2 support

Integrates easily with standard enterprise management systems

Ad hoc mode (CB3000 to CB3000 – networking of all connected devices)

Quickly and inexpensively enable the sharing of printers and other peripherals, server access and more

An ideal companion for your mobility solution

The CB3000 — a flexible and very economical wireless connection enabling the movement of data to and from many types of devices, with the reliability, performance and security you expect in Motorola enterprise mobility solutions. Motorola Enterprise Mobility Services also offers the

comprehensive support and technical expertise you need to design, deploy and maintain the most successful mobility solutions.

For more information about the CB3000, access our global contact directory at www.symbol.com/ contact or visit us on the web at www.symbol.com/

CB3000 Specifications

Physical Characteristics

Dimensions:	7.0 in. L x 4.0 in. W x 1.2 in. D 179 mm L x 102 mm W x 31 mm D
Interfaces:	Ethernet Interface: RJ-45 10/100Base-T; 802.11a/b/g
LEDs:	Power (Status/Error), WLAN (802.11a/802.11g), LAN (10/100 Mb)
Operating Temp:	32° to 122° F/0° to 50° C
Humidity:	10% – 90% non-condensing

Software Specifications

Security:	WPA2/802.11i; 802.1x Supplicant, PEAP, EAP/TLS, EAP/TLS, Client Access Control List
Network Protocol Support:	TCP/IP, DHCP, SNMP v2
Network Management:	Embedded Secure Web server; SNMP v2 support, Discovery Tool included for all bridges in Layer 2 network
POS Protocol Support:	RPL, PXE; Limit one RPL or PXE terminal per bridge
Standards:	IEEE 802.11a/b/g; IEEE 802.3; IEEE 802.1d; 802.11i; 802.11h (DFS/TCP); HTTPS

Compatibility

Supported Devices:	Windows-based PCs equipped with Ethernet cards; point-of-sale devices; network printers; thin clients; Mac/Apple machines; Linux/Unix workstations; Ethernet-enabled appliances; and/or mix of all devices listed
Device Manager:	Windows 2000, Windows XP

Radio Characteristics

Frequency Range:	802.11a: 5.150—5.825 GHz 802.11b/g: 2.4—2.4835 GHz
Data Rate:	802.11a/g: 54, 48, 35, 24, 18, 12, 9 and 6 Mbps 802.11b: 11, 5.5, 2 and 1 Mbps
Part Number:	CB-3000-0010-WWR
Approved Antennas:	ML-2452-APA2-01R 3dBi/4dBi Dual Band Omni-Directional (included) ML-2499-HPA3-01 5 dBi 802.11b/g Omni-Directional ML-2499-SD3-01 Patch antenna, 3 dBi, 2.4 GHz ML-2499-BYGA2-01 Yagi bridge antenna, 15 dBi, 35 deg beam ML-5299-HPA1-01 Omni Antenna, 5 dBi, 5 GHz ML-5299-WPNA1-01 Wall Mounting Panel Antenna, 5 GHz

Radio Sensitivity:	802.11b 1 Mbps –97 dBm 2 Mbps –93 dBm 5.5 Mbps –91 dBm 11 Mbps –85 dBm 802.11a 6 Mbps –90 dBm 9 Mbps –88 dBm 12 Mbps –87 dBm 18 Mbps –85 dBm 24 Mbps –81 dBm 36 Mbps –79 dBm 48 Mbps –73 dBm 54 Mbps –72 dBm	802.11g 6 Mbps –91 dBm 9 Mbps –89 dBm 12 Mbps –89 dBm 18 Mbps –85 dBm 24 Mbps –84 dBm 36 Mbps –80 dBm 48 Mbps –76 dBm 54 Mbps –74 dBm
Nominal Transmitter Power:	802.11b/g 20.5 dBm+1/-1.5 dBm @ 1, 2, 5.5, 11 Mbps 20.5 dBm +1/-1.5 dBm @ 6, 9, 12, 18, 24 Mbps 18.5 dBm +1/-1.5 dBm @ 36 Mbps 17.5 dBm +1/-1.5 dBm @ 48 Mbps 16.5 dBm +1/-1.5 dBm @ 54 Mbps 802.11a 20.5 dBm +1/-1.5 dBm @ 6, 9, 12, 18, 24 Mbps 16.5 dBm +1/-1.5 dBm @ 36 Mbps 15.5 dBm +1/-1.5 dBm @ 48 Mbps 14.5 dBm +1/-1.5 dBm @ 54 Mbps	
Modulation:	DSSS (Direct Sequence Spread Spectrum) OFDM (Orthogonal Frequency Division Multiplexing)	
Range:	Up to 1,000 ft./300 m in open environment (range varies based on environment)	
Regulatory		
Electrical and Mechanical Safety:	cUL1950; EN60950 and IEC60950	
EMC:	FCC Part 15B; ICES-003 Class B; EU EN 301 489 Parts 1 & 17; EN 60601-1-2 (Medical)	
Radio:	FCC Part 15.247, 15.205, 15.209, 15.207, 15.203, 15.407; Canada: RSS-210; EU EN 300 328 (2.4GHz), EN 301 893 (5GHz); Japan ARIB STD-66, 33 & T71	



VisionID Ltd
Unit 2,
Carrigeen Business Park,
Clonmel,, Ireland IE
www.visionid.ie
Phone: 00353 5261 81858



MOTOROLA

PartnerSelect
Solution Partner